



## 2005 To 2008 Jeep Grand Cherokee And Commander Class 2 Trailer Hitch By Hidden Hitch 90114

Black powder coat finish. Class 2 / II, 1 1/4 inch x 1 1/4 inch receiver opening. All hardware and instructions included. Note: Receiver ball mount bar is included. Wiring harness and trailer hitch ball sold separately. Manufactured by Hidden Hitch.

**Weight Carrying:** 300/3500 lbs.(TW/GTW)

**Weight:** 15 lbs.

### Applications:

2006-2008 Jeep Commander

2005-2008 Jeep Grand Cherokee All, Except SRT-8

### Tools Required:

Wrenches: 3/4"

**Note:** For vehicles with OEM Tow Hooks: Tow hook must be permanently removed for hitch installation. Drawbar must be used in the DROP position only.

### Installation Instructions:

1. Lower the spare tire.
2. Remove two plastic pins that hold bumper fascia onto bumper structure. (If OEM tow hook is present: Remove fascia, plastic bumper support and tow hook)
3. Gently pull fascia rearward about one inch and raise the hitch into position.
4. If there is excessive gap between the vertical surfaces of the hitch and the bumper structures, flat washers should be used as shims. They can be held in place using cellophane tape.
5. Secure hitch with fasteners. Fascia may contact the back of the hitch. (Reinstall fascia and plastic bumper support if removed in Step 2.)
6. Replace plastic pins in bumper fascia.
7. Raise the spare tire into storage position.
8. Tighten all 1/2-13 GR5 fasteners with torque wrench to 75 Lb.-Ft. (120 N\*M)